



PROSTAR

- > 500 CD Capacity allows reliable, high-volume, lights-out production.
- > Intelligent and Efficient dual-handed, rotary picker uses concise actions to deliver unmatched robotic speed.
- > Permanent thermal printing that dries instantly to support high-volume productions.
- > Data-Merging Flexibility using proprietary architecture that supports up to 8 unique data streams allowing concurrent network downloading, imaging and recording in a single unit.
- > Industry-Leading Throughput creates scores of unique CDs in minutes, in both CD-R and DVD-R format, utilizing Rimage's data-streaming technology.
- > ProNet Software Platform is the next generation, all-encompassing software suite. The multi-functional platform provides unmatched performance in the production of CD-Rs and DVD-Rs. ProNet provides all the tools necessary for disc duplication and disc publishing, with simplified integration into existing systems.
- > Revolutionary Anti-Piracy Plug-In Architecture developed by Rimage gives you control over your content. Encrypted Digital Fingerprinting™ (EDF) plug-in is a standard feature that places numerous traceable, undetectable watermarks on the disc. These digital fingerprints survive duplication, even re-imaging. Optional plug-ins allow the use of third-party anti-piracy software, giving you unmatched flexibility.

SPECIFICATIONS

data streaming. robotics. printing.

Standard System

Up to 8 Industry Standard CD-R Recorders; Rimage Prostar, Prism CD-R Surface Printer, Perfect Print™, CD-R Control Center, ProNET Software Suite

Options

Second Printer with a single system
Rack mounted control center
DVD-R –or– DVD-R/CD-R Combination System

CD Printer

600 x 300 dpi color thermal transfer CD Printer
(Detailed specifications on the printer are available.)

Ribbons

Monochrome colors in black, red or blue; 2-color panel ribbon in blue/black, red/black or green/black; or 3-color panel ribbon

Imageable formats

The Imaging Server Software can create ISO 9660 images (Level 1: Level 1, Relaxed: Level 2, Joliet). Macintosh HFS, Hybrid ISO 9660/HFS and ISO 9660 with Apple® Extensions images, Rockridge

Recordable Formats

CD-DA (Red Book Audio)
CD-ROM (Yellow Book Mode 1)
CD-ROM XA (Mode 2 Form 1, Mode 2 Form 2, Mode 2 with interleaved Form 1 and Form 2)
CD-I
Mixed Mode (CD-ROM and CD-DA)
Multisession (both independent and incremental)
Track-at-once and disc-at-once are supported

Power

Prostar 100–240 VAC, 60/50 Hz, 6.7–3.4 Amp, 800 watt maximum
Control Center 100–120/200–240 VAC, 60/50 Hz, 6/3 Amp
Monitor 100–240 VAC, 60/50 Hz, 1.2–0.6 Amp

Relative Humidity

40%–80% noncondensing

Bin Capacities

Three 250-disc spindles configurable as input, input, output.
Separate reject spindle. Maximum I/O capacity is 500 discs.
System can facilitate the use of standard bulk spindle(s) for output. Standard Rimage spindles must be used for input.
I/O capacity varies depending on the configuration.

Physical

Prostar 31" H x 18" W x 31" D
(83cm H x 51cm W x 83cm D) 170 lbs. (78Kg)
Control Center 18" H x 10" W x 23" D
(46cm H x 20cm W x 46cm D) 35 lbs. (16Kg)
Rack mount pc option 5" H x 18" W x 29" D
(13cm H x 46cm W x 74cm D)
Monitor 15" H x 15" W x 17" D
(38cm H x 38cm W x 43cm D) 30 lbs. (14Kg)

Operating Temperature

60°F–86°F (15.5°C–30°C). Limited by recorder.

Certifications

Emissions FCC Class B, EN55022 Class B
Susceptibility EN55024 Class B
Safety UL1950, CANS22.2 No. 950, EN60950
Conformance Marks UL, cUL, CE (Prostar)
UL, CSA, CE, TUV (Control Center, Monitor)

Warranty

One-year limited depot (U.S.A.)

Service Options

Various Rimage Service Programs are available
Contact your local Rimage Service Representative for details

All Rimage products proudly feature Dell® computer products carrying a 3-year warranty.



R I M A G E™

Rimage Corporation
7725 Washington Avenue South
Minneapolis, MN 55439 USA
phone: 952/944.8144
fax: 952/944.7808
www.rimage.com

Rimage Europe GmbH
Hans-Böckler-Straße 7
63128 Dietzenbach
Germany
phone: 49.0.6074.8521.0
fax: 49.0.6074.8521.21
www.rimage.de